


TA-Aluform® Trapezoidal Profile 29/124 for roof & wall

Product Data Sheet

Material	Stainless steel AISI 304	
Surface	2B matt, BA bright annealed	
Backside finish	Anti-drip fleece, acoustic fleece	
Length	500 to 10,500 mm available ex works (special lengths on request)	
Perforation	Rv 3-5, Rv 5-8 (other hole patterns on request)	
Building material class	A1	

Thickness / mm	Weight / kg/m²	Coil width / mm
0.5	5.060	1250
0.6	6.072	1250



The Best Part 01 | 10.2025

Tacke + Lindemann GmbH

Beratgerstraße 31-33 | 44149 Dortmund

Tel +49 (0)23117777-0 Fax +49 (0)23117777-50 info@tacke-lindemann.de www.tacke-lindemann.de

Disclaimer

Our products are based on careful research and reflect the current state of the art. The data and information are provided to the best of our knowledge, but without guarantee. All values given are average values, not maximum or minimum values, and do not constitute a guarantee. Changes and deviations are possible; we expressly reserve the right to make technical adjustments.

It is the responsibility of the user to independently check the suitability of the product for the respective application before use.

We accept no liability for errors, inaccuracies, omissions or changes. Furthermore, the applicable regulations, rules and DIN standards must be observed.

The use of texts, images and drawings, even in part, is not permitted without consent.

Our General Terms and Conditions (GTC) apply exclusively.