



TA-Aluform® Trapezoidal Profile 40/183 for roof & wall

Product Data Sheet

Steel S 320 GD
Galvanised steel Z 275, Aluzinc AZ 185
Lacquering (polyester, PVdF, HDP)
Protective lacquer, anti-drip fleece, acoustic fleece
500 to 10,500 mm available ex works (special lengths on request)
Rv 3-5, Rv 5-8 (other hole patterns on request)
T25-012
A1

Thickness / mm	Weight / kg/m²	Coil width / mm
0.63	6.915	1250
0.75	8.232	1250
1.0	10.976	1250





01/10/2025 The Best Part

Tacke + Lindemann GmbH

Beratgerstraße 31-33 | 44149 Dortmund

Tel +49 (0)231 17 77 7-0
Fax +49 (0)231 17 77 7-50
E-Mail info@tacke-lindemann.de
Web www.tacke-lindemann.de

Disclaimer

Our products are based on careful research and reflect the current state of the art. The data and information are provided to the best of our knowledge, but without guarantee. All values given are average values, not maximum or minimum values, and do not constitute a guarantee. Changes and deviations are possible; we expressly reserve the right to make technical adjustments.

It is the responsibility of the user to independently check the suitability of the product for the respective application before use.

We accept no liability for errors, inaccuracies, omissions or changes. Furthermore, the applicable regulations, rules and DIN standards must be observed.

The use of texts, images and drawings, even in part, is not permitted without consent.

Our General Terms and Conditions (GTC) apply exclusively