

## Declaration of Performance




in accordance with the EU Construction Products Regulation of 2020  
 Reference number NB2457  
 FB 1.129/06-26-EN  
 2457-CPR-0020

1	Trapezoidal profile made of aluminium Rp 0.2: 195 N/mm <sup>2</sup> , Rm: 215 N/mm <sup>2</sup>
2	<b>40/183 from 0.5 – 1.2 mm</b>
3	Self-supporting trapezoidal profile for roof and façade according to EN 1090-5:2020
4	<b>Tacke + Lindemann GmbH Beratgerstr. 31-33 44149 Dortmund</b>
6	System 2+
7	<b>Manufacturer's declaration</b> regarding the implementation of initial type testing and in-house production control
9	Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
<b>Sheet thickness</b>	0.5 – 1.2 mm, Class 2 According to EN 1090-5:2020	EN 1090-1-2020
<b>Dimensional tolerances</b>	Compliant with EN 1090-5:2020	
<b>Dimensional change</b>	Coefficient of thermal expansion Aluminium: $24 \times 10^{-6} \text{ K}^{-1}$	
<b>Reaction to fire</b>	A1	
<b>Durability</b>	Aluminium mill finish   stucco   coated	
<b>Load capacity</b>	According to general type approval Nr. Z-14.1-545	
<b>Fire resistance</b>	NPD	
<b>Release of Cadmium</b>	NPD	
<b>Release of radioactive radiation</b>	NPD	

10 The performance of the product as stated in items 1 and 2 corresponds to the declared performance in item 9. The manufacturer listed under item 4 is solely responsible for the preparation of this declaration of performance.  
 Signed for and on behalf of the manufacturer:  
 Michael Jakoby, Authorized Signatory

Dortmund, 17.06.2026

  
 \_\_\_\_\_  
 ppa. Michael Jakoby